

**HOOK-UP WIRE**

CSA TEW

**Description:**

Stranded Tinned Copper, Color Coded Polyvinylchloride Insulation, .032" Nominal Insulation Thickness

Characteristics:

Temperature Rating: -40°C to +105°C - Passes UL WW-1 Flame Test

Voltage Rating: 600V, AWM 10269 is Rated for 1000V (2 AWG ONLY)

WEICO NO.	CONDUCTOR		NOM. O.D. (IN)
	SIZE	STRAND	
3224	24	7/2	.088
3222	22	7/0	.095
3220	20	10/30	.102
3218/1	18	Solid	.104
3218	18	16/30	.112
3216	16	26/30	.125
3214	14	41/30	.142
3212	12	65/30	.156
3210	10	105/30	.184
3208 *	8	133/29	.265
3206 **	6	133/27	.341
3204 **	4	133/25	.388
3202**	2	7x95/30	.424

****Please note 2 AWG is only available in Black, Red & Brown****

***UL 1028, .047" wall thickness**

****UL 1283, .063" wall thickness**

COLORS:

0 - Black, **1** - Brown, **2** - Red

3 - Orange, **4** - Yellow, **5** - Green

6 - Blue, **7** - Violet, **8** - Gray, **9** - White

X Denotes 0 - 9 color coding

STRIPES:

Any of the above colors are available in any combination of stripes up to a maximum of three stripes.

Standard Put-Ups: 100 ft., 1000 ft.