

MULTICONDUCTOR CABLE

MULTICONDUCTOR
UNSHIELDED

800°C-300V-PVC



Description:

Each Conductor Stranded Tinned Copper, Color Coded Polyvinylchloride Insulation. Gray Polyvinylchloride Jacket Overall.

Specifications:

UL Listed, NEC Type CM or CL2 (see table), 75°C
 UL AWM Style 2095, 80°C, 300V
 CSA Certified PCC FT-4

WEICO NO.	NO. OF COND.	NOM. JACKET THICKNESS (INCHES)	UL NEC RATING	NOM. O.D. (IN)
20 AWG (10/30) Nom. Insulation Thickness .016				
4002/20	2	.020	CL2	.180
4003/20	3	.020	CL2	.190
4004/20	4	.020	CL2	.215
4005/20	5	.020	CL2	.233
4006/20	6	.020	CL2	.255
4007/20	7	.020	CL2	.255
4008/20	8	.020	CL2	.270
4009/20	9	.020	CL2	.300
4010/20	10	.020	CL2	.335
4012/20	12	.020	CL2	.350

WEICO NO.	NO. OF COND.	NOM. JACKET THICKNESS (INCHES)	UL NEC RATING	NOM. O.D. (IN)
4015/20	15	.020	CL2	.395
18 AWG (16/30) Nom. Insulation Thickness .016				
4002/18	2	.020	CM	.200
4003/18	3	.020	CM	.210
4004/18	4	.020	CM	.240
4005/18	5	.020	CM	.262
4006/18	6	.020	CM	.290
4007/18	7	.020	CM	.286
4008/18	8	.025	CM	.315
4009/18	9	.025	CM	.346
4010/18	10	.025	CM	.370
4012/18	12	.025	CM	.385
4015/18	15	.030	CM	.445
4019/18	19	.030	CM	.470
4025/18	25	.035	CM	.558
16 AWG (26/30) Nom. Insulation Thickness .016				
4002/16	2	.020	CL2	.225
4003/16	3	.020	CL2	.245
4004/16	4	.020	CL2	.270

Standard Put-Ups: 100 ft., 500 ft., 1000 ft.