

# WELDING CABLE AND PORTABLE CORD



## PORTABLE CORDS

300-600V  
SJO, SO

### Description:

Each Conductor Stranded Bare Copper, Color Coded Rubber Insulation, Cabled with Fillers, Separator, Black Neoprene Jacket Overall.

### Characteristics:

Temperature Range: -30°C to +90°C

Voltage Rating:

SJO: 300V

SO: 600V

WEICO NO.	TYPE	NO. OF CONDUCTORS	AWG	NOM. INS. THICK.	NOM. JKT. THICK.	CURRENT CAPACITY IN AMPS	NOM. O.D. (IN)
Neoprene Portable Cord 300 Volt							
NJO-218	SJO	2	18	.032	.032	7	.305
NJO-318	SJO	3	18	.032	.032	7	.330
NJO-216	SJO	2	16	.032	.032	10	.330
NJO-316	SJO	3	16	.032	.032	10	.360
Neoprene Portable Cord 600 Volt							
NO-218	SO	2	18	.030	.060	7	.390
NO-318	SO	3	18	.030	.060	7	.405
NO-418	SO	4	18	.030	.060	6	.435
NO-216	SO	2	16	.030	.060	10	.405

WEICO NO.	TYPE	NO. OF CONDUCTORS	AWG	NOM. INS. THICK.	NOM. JKT. THICK.	CURRENT CAPACITY IN AMPS	NOM. O.D. (IN)
NO-316	SO	3	16	.030	.060	10	.430
NO-416	SO	4	16	.030	.060	8	.485
NO-214	SO	2	14	.045	.075	15	.530
NO-314	SO	3	14	.045	.075	15	.560
NO-414	SO	4	14	.045	.075	12	.605
NO-212	SO	2	12	.045	.090	20	.600
NO-312	SO	3	12	.045	.090	20	.635
NO-412	SO	4	12	.045	.090	16	.665
NO-210	SO	2	10	.045	.090	25	.640
NO-310	SO	3	10	.045	.090	25	.690
NO-410	SO	4	10	.045	.090	20	.745

**COLOR CODE: 1 -White, 2 - Black, 3 - Green, 4 - Red**  
**Standard Put-Up: 250 ft**