

MULTIPAIR CABLE

MULTIPAIR
FOIL SHIELD
300V - 22 GAUGE



Description:

Each Conductor Stranded Tinned Copper, Color Coded Polyvinylchloride (UL Style 1061) Insulated. Twisted into pairs. Overall Aluminum/Polyester Shield with Stranded Tinned Copper Drain Wire, Nylon Rip Cord for Ease of Jacket Stripping, Gray PVC Jacket Overall

Specifications:

UL Listed, NEC Type CM, 75°
UL AWM Style 2464, 80°C, 300V
CSA Certified PCC FT-4
OSHA Acceptable

WEICO NO.	NO. OF PAIRS	NOM. JACKET THICKNESS (INCHES)	NOM. O.D. (IN)
#22 AWG (7/30) Nom. Ins. Thickness .010"			
7702	1	.032	.180
7704	2	.032	.230
7706	3	.032	.260
7708	4	.032	.280
7710	5	.032	.310
7712	6	.032	.330
7718	9	.032	.380
7722	11	.032	.410
7730	15	.032	.460

WEICO NO.	NO. OF PAIRS	NOM. JACKET THICKNESS (INCHES)	NOM. O.D. (IN)
7738	19	.032	.500
7754	27	.053	.610
7701	51	.083	.860

Standard Put-Ups: 100 ft., 500 ft., 1000 ft.