

MULTICONDUCTOR CABLE

MULTICONDUCTOR
FOIL SHIELD

60°C-PE/PVC-300V



Description:

Each Conductor Stranded Tinned Copper, Color Coded Polyvinylchloride Insulation. Gray Polyvinylchloride Jacket Overall.

Specifications:

UL Listed, NEC Type CM or CL2, 75°C
UL AWM Style 2092, 2093, 2094*, 60°C, 300V

WEICO NO.	NO. OF COND.	NOM. WALL THICKNESS	NOM. O.D. (IN)	UL NEC RATING	COND. COLOR CODE
24 AWG (7/32) NOM. INSULATION THICKNESS .016					
9201	2	.020	.160	CM	1,3
22 AWG (7/30) NOM. INSULATION THICKNESS .016					
9202	2	.020	.170	CM	1,3
9203	2	.020	.170	CM	1,2
9204	3	.020	.185	CM	1,2,3
9205	4	.020	.210	CM	1,2,3,4
20 AWG (10/30) NOM. INSULATION THICKNESS .016					
9206	2	.020	.186	CL2	1,3
9207	2	.020	.186	CL2	1,2
9208	3	.020	.205	CL2	1,2,3
9209	4	.020	.225	CL2	1,2,3,4

WEICO NO.	NO. OF COND.	NOM. WALL THICKNESS	NOM. O.D. (IN)	UL NEC RATING	COND. COLOR CODE
18 AWG (16/30) NOM. INSULATION THICKNESS .016					
9210	2	.020	.210	CM	1,3
9211	2	.020	.210	CM	1,2
9212	3	.020	.230	CM	1,2,3
9214	4	.020	.255	CM	1,2,3,4
16 AWG (26/30) NOM. INSULATION THICKNESS .016					
9215	2	.020	.245	CL2	1,2
9216	3	.020	.270	CL2	1,2,3

*2 Cond. - UL 2092, 3 Cond. - UL 2093, 4 Cond. - UL 2094

COLORS:

1 - Black, 2 - Red, 3 - Clear, 4 - Green

Standard Put-Ups: 100 ft., 500 ft., 1000 ft.