

HOOK-UP WIRE



THHN UNIVERSAL CIRCUIT WIRE 600V

Description:

Stranded or Solid Bare Copper, PVC Insulation and Clear Nylon Jacket Overall. Used for Building Wire, Machine Tool Wire, Appliances, Lighting Ballasts and General Hook-Up Wire.

Characteristics:

Temperature Rating: +105°C

Voltage Rating: 600V

WEICO NO.	CONDUCTOR		INSULATION THICKNESS	NOM. JACKET THICKNESS	NOM. O.D. (IN)
	SIZE	STRAND			
8928	18	Solid	.015	.004	.082
1430	16	Solid	.015	.004	.089
1431	14	Solid	.015	.004	.110
1432	12	Solid	.015	.004	.125
1433	10	Solid	.020	.004	.155
1429 *	18	19	.015	.004	.090
1434 *	16	19	.015	.004	.100
1435	14	19	.015	.004	.116
1436	12	19	.015	.004	.135
1437	10	19	.020	.004	.170
1438	8	19	.030	.005	.225
1439	6	19	.030	.005	.260

WEICO NO.	CONDUCTOR		INSULATION THICKNESS	NOM. JACKET THICKNESS	NOM. O.D. (IN)
	SIZE	STRAND			
1440	4	19	.040	.006	.335
1441	2	19	.040	.006	.400
1442	1	19	.050	.007	.450
1443	1/0	19	.050	.007	.500
1444	2/0	19	.050	.007	.540

*TFFN

COLORS:

0 - Black, 1 - Brown, 2 - Red
3 - Orange, 4 - Yellow, 5 - Green
6 - Blue, 7 - Violet, 8 - Gray, 9 - White

STRIPES:

Any of the above colors are available in any combination of stripes up to a maximum of three stripes.

Standard Put-Up: #18 Thru #6 - #500 ft. #4 & Larger - 100 ft.