



HOOK-UP WIRE



MIL-W-16878/3

TYPE D - 3000V

Description:

Stranded Tinned Copper, Color Coded Polyvinylchloride Insulation

Characteristics:

Temperature Rating: -55°C to +105°C

Voltage Rating: 3000V

Passes UL VW-1 Flame Test

WEICO NO.	MILITARY NO.	CONDUCTOR		NOM. WALL THICKNESS	NOM. O.D. (IN)
		SIZE	STRAND		
1324	M16878/3BEB-X	24	7/32	.029	.082
1322	M16878/3BFB-X	22	7/30	.029	.088
1320	M16878/3BGB-X	20	7/28	.029	.096
1318	M16878/3BHB-X	18	7/26	.029	.106
1316/19	M16878/3BJE-X	16	19/29	.029	.115
1314/19	M16878/3BKE-X	14	19/27	.029	.129
1312/19	M16878/3BLE-X	12	19/25	.034	.158
1310	M16878/3BMG-X	10	37/26	.037	.185
1308	M16878/3BNL-X	8	133/29	.040	.247
1306	M16878/3BPL-X	6	133/27	.040	.290
1304	M16878/3BRL-X	4	133/25	.046	.358
1302	M16878/3BSP-X	2	665/30	.046	.432

COLORS:

0 - Black, **1** - Brown, **2** - Red

3 - Orange, **4** - Yellow, **5** - Green

6 - Blue, **7** - Violet, **8** - Gray, **9** - White

X Denotes 0 - 9 color coding

STRIPES:

Any of the above colors are available in any combination of stripes up to a maximum of three stripes.

Standard Put-Ups: 100 ft., 1000 ft.