



HOOK-UP WIRE



MIL-W-16878/2

TYPE C - 1000V

Description:

Stranded Tinned Copper, Color Coded Polyvinylchloride Insulation

Characteristics:

Temperature Rating: -55°C to +105°C

Voltage Rating: 1000V

Passes UL VW-1 Flame Test

WEICO NO.	MILITARY NO.	CONDUCTOR		NOM. WALL THICKNESS	NOM. O.D. (IN)
		SIZE	STRAND		
1224/1	M16878/2BEA-X	24	Solid	.016	.052
1224	M16878/2BEB-X	24	7/32	.016	.058
1222/1	M16878/2BFA-X	22	Solid	.016	.057
1222	M16878/2BFB-X	22	7/30	.016	.064
1220/1	M16878/2BGA-X	22	Solid	.016	.064
1220	M16878/2BGB-X	20	7/28	.016	.072
1218	M16878/2BHB-X	18	7/26	.016	.082
1216/19	M16878/2BJE-X	16	19/29	.016	.091
1214/19	M16878/2BKE-X	14	19/27	.016	.105
1212/19	M16878/2BLE-X	12	19/25	.016	.124

COLORS:

0 - Black, **1** - Brown, **2** - Red

3 - Orange, **4** - Yellow, **5** - Green

6 - Blue, **7** - Violet, **8** - Gray, **9** - White

X Denotes 0 - 9 color coding

STRIPES:

Any of the above colors are available in any combination of stripes up to a maximum of three stripes.

Standard Put-Ups: 100 ft., 1000 ft.