




HOOK-UP WIRE

MIL-W-16878/6
SOLID CONDUCTOR
TYPE ET-250V



Description:

Solid Silver Plated Copper, Extruded PTFE Insulation

Characteristics:

Temperature Rating: -60°C to +200°C
Voltage Rating: 250V
Passes UL VW-1 Flame Test

| WEICO NO. | MILITARY NO. | CONDUCTOR | | NOM. WALL THICKNESS | NOM. O.D. (IN) |
|-----------|---------------|-----------|--------|---------------------|----------------|
| | | SIZE | STRAND | | |
| 2932 | M16878/6BAA-X | 32 | Solid | .006 | .019 |
| 2930 | M16878/6BBA-X | 30 | Solid | .006 | .022 |
| 2928 | M16878/6BCA-X | 28 | Solid | .006 | .025 |
| 2926 | M16878/6BDA-X | 26 | Solid | .006 | .028 |
| 2924 | M16878/6BEA-X | 24 | Solid | .006 | .032 |

COLORS:

0 - Black, 1 - Brown, 2 - Red
3 - Orange, 4 - Yellow, 5 - Green
6 - Blue, 7 - Violet, 8 - Gray, 9 - White
X Denotes 0 - 9 color coding

STRIPES:

Any of the above colors are available in any combination of stripes up to a maximum of three stripes.

Standard Put-Ups: 100 ft., 1000 ft.