



HOOK-UP WIRE



MIL-W-16878/6

TYPE ET-250V

**Description:**

Stranded Silver Plated Copper, Extruded PTFE Insulation.

Characteristics:

Temperature Rating: -60°C to +200°C

Voltage Rating: 250V

Passes UL VW-1 Flame Test

WEICO NO.	MILITARY NO.	CONDUCTOR		NOM. WALL THICKNESS	NOM. O.D. (IN)
		SIZE	STRAND		
2332	M16878/6BAB-X	32	7/40	.006	.021
2330	M16878/6BBB-X	30	7/38	.006	.024
2328	M16878/6BCB-X	28	7/36	.006	.027
2328/19	M16878/6BCE-X	28	19/40	.006	.027
2326	M16878/6BDB-X	26	7/34	.006	.031
2326/19	M16878/6BDE-X	26	19/38	.006	.032
2324	M16878/6BEB-X	24	7/32	.006	.036
2324/19	M16878/6BEE-X	24	19/36	.006	.037
2322	M16878/6BFB-X	22	7/30	.006	.042
2322/19	M16878/6BFE-X	22	19/34	.006	.044
2320/19	M16878/6BGE-X	20	19/32	.006	.050

COLORS:

0 - Black, **1** - Brown, **2** - Red

3 - Orange, **4** - Yellow, **5** - Green

6 - Blue, **7** - Violet, **8** - Gray, **9** - White

X Denotes 0 - 9 color coding

STRIPES:

Any of the above colors are available in any combination of stripes up to a maximum of three stripes.

Standard Put-Ups: 100 ft., 1000 ft.